

(19) World Intellectual Property
Organization
International Bureau



552 211

(43) International Publication Date
21 October 2004 (21.10.2004)

PCT

(10) International Publication Number
WO 2004/090240 A1

(51) International Patent Classification⁷: **E02D 27/01**,
27/02

(21) International Application Number:
PCT/CZ2003/000051

(22) International Filing Date:
18 September 2003 (18.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PV 2003-1002 10 April 2003 (10.04.2003) CZ

(71) Applicant and

(72) Inventor: BENDA, Jirí [CZ/CZ]; Ing.Jirí Benda, Pozár-
nická 45/50, 748 01 Hlucín-Bobrovňky, okres Opava (CZ).

(74) Agent: RYLKOVÁ, Iva; Ing.Iva Rylková, Polská 1525,
708 00 Ostrava-Poruba (CZ).

(81) Designated States (national): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,

CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (util-
ity model), DE, DK (utility model), DK, DM, DZ, EC, EE,
EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN,
IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM,
PG, PH, PL, PT (utility model), PT, RO, RU, SC, SD, SE,
SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT,
TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF MAKING A FLAT FOUNDATION FOR A FLOOR WITHOUT SUBSTANTIAL EXCAVATION AND
FOUNDATION MADE BY SAID METHOD



(57) Abstract: Cellular foil (3) is unfolded between the surface of earth base course (1) and the first floor layer (5) during building the subsoil, which cellular foil (3) is poured over with fill (4) from loose material at least up to filling the compartments. A bedding (2) from loose material, optimally from sand, is created under the cellular foil (3). Geotextile (6) may be incorporated to the area under the cellular foil (3). Bedding (2) of lower grain size than that of the fill (4) is preferably used, wherein the fill (4) has optimal grain size of 8 to 63 mm. Compaction is done by at least eight travels of roller of 10 to 11 tons weight, also including vibrations when the height of fills is exceeding 25 cm above the cellular foil (3).

WO 2004/090240 A1